

Neumos

Capitol Hill, Seattle

FOH CONSOLE	Venue SC48 Digital Protocols console
FOH SPEAKERS	(10) JBL VTX V20 - LINE ARRAYED (4) JBL AC28 Fills (8) JBL VTX S25 Dual 15 Sub
POWER AMPLIFICATION	Crown 3500HD, Crown XTi6002
MONITOR CONSOLE	Midas Pro2
MONITORS	(12) JBL STX812M, (1) JBL STX 818S Drum Sub
STEREO SIDE FILL MONITORS	(2) JBL STX835 Sidefills
MICROPHONES AND DI'S	(2) Shure Beta 91A (2) Shure Beta 52A (2) Shure Beta 58 (2) Shure Beta 57 (8) Shure SM 57 (8) Shure SM 58 (2) Shure SM 94 (1) AUDIX d6 (6) Sennheiser E604 (4) Sennheiser E609 (4) Shure ULX Wireless mics (12) Radial ProDI Passive DI (4) Radial D2 Passive Stereo DI

Technical Specifications | _____

LIGHTING BOARD - AVOLITES QUARTZ | _____

LIGHTING	(18) Chauvet Par-Quad 18 LEDs (6) Chauvet NXT-1 Moving Head LED Panel (6) Chauvet R1-Beam Moving Head (1) Martin-Rush MH3 Beam (1) Martin Atomic Strobe (6) Chauvet ovation E-190WW
STAGE DIMENSIONS	23.5' Wide – 16' Deep – 3' Tall Clearance: 9.5' to lights – 11' to truss
FLOOR TO CEILING	16'

Neumos Venue Power

This is a 110/208/240 Delta service and we have 3-phase power via a transformer

Lights – House Lights draw from this power (separate from Audio)

3 Ø – 60 amps / leg = 180 Amps

Cam Locs – Tour must supply any necessary neutral / ground cam loc turnarounds.

Additional power available on-site (separate from House Lights)

(1) 20 Amp / 110v circuit Stage Left

(2) 20 Amp / 110v circuit Stage Right

Audio – House Sound draws from this power (separate from Lights)

(6) 30 Amp circuits total for stage power/PA

(6) 20 Amp circuits